



Rugged ■ Reliable ■ Weatherproof

EnergyPro EP600

Energy Datalogger

RMS Data • Min, Max, and Average RMS data storage.

Power Quality • THD, Harmonics, Voltage and Current Unbalance.


Connection Type • 1P2W, 1P3W, 3P3W, 3P4W, 2.5Element.

Power Calculations

- KW, KVA, KVAR, KWHR, KW/HR.
- Displays total and average energy usage (KWHR and KW/HR) during the survey.
- True Power Factor (KW divided by KVA).

Voltage	V1,V2,V3	0 - 600 VAC
Current	CT1, CT2, CT3	10 - 3000A Clamp CT Auto Ranging 0.2A - 2500A Flex CT
Frequency	45 - 65 Hz	
Accuracy	Voltage: 0.5% of full scale Current: 0.5% of full scale	
Storage Rate	1 second to 30 minutes	
Battery Backup	5 days run time Data backup infinite	
Memory	1G removable memory cards	
Operating Temperature	-20°C to 60°C	

* Specifications subject to change without notice



	KW	KVA	KVAR
W	228.4	235.5	57.4
V	229.4	229.0	55.9
C	229.3	234.0	46.7
T	681	699	160

KWHR

TOTAL KWHR
3014.00
AVG KW/HR
109.49

Now Auto Ranging 0.2A - 2500A

